

CT-5361T

Wireless ADSL2+ Router



Description


The CT-5361T is an 802.11g (54Mbps) Wireless and Wired ADSL2+ router. Four 10/100 Base-T Ethernet ports and an optional USB port and an integrated 802.11g WiFi WLAN Access Point (AP) provide with wired LAN connectivity and wireless connectivity separately.

The CT-5361T ADSL2+ router also provides for state of the art security features such as WPA data encryption, Firewall and VPN pass through. The CT-5361T is designed for both residential and business applications that require wireless and wired connectivity to an ADSL broadband network. The CT-5361T supports up to 16 contiguous virtual connections allowing for multiple simultaneous Internet connections. The CT-5361T is also designed with TR-068 compliant color panel and LED indicators, which eases the installation of the modem and makes it more user-friendly.

Features

- CT-5361T (Annex A)
- UPnP
- Integrated 802.11g AP (Backward compatible with 802.11b)
- WPA/WPA2 and 802.1x
- Optional Turbo mode in wireless (After burner)
- WMM
- RADIUS client
- MAC address filtering
- IP filtering
- Static route/RIP/RIP v2 routing functions
- Dynamic IP assignment
- IP QoS
- IGMP Proxy
- DHCP Server/Relay/Client
- DNS Proxy
- Auto PVC configuration
- Per-VC packet level QoS
- Up to 16 VCs
- Embedded SNMP agent
- Web-based management
- Supports remote administration, automatic firmware upgrade and configuration
- Configuration backup and restoration
- FTP/TFTP server
- Supports TR-069/TR-098/TR-111 for remote management
- TR-068 compliant

Applications Diagram



CT-5361T

Wireless ADSL2+ Router



Specifications

Hardware Interface

RJ-11 X1 for ADSL, RJ-45 X 4 for LAN, USB X 1 for LAN, Reset button X 1, Power switch X 1, Wi-Fi Antenna X 1

WAN Interface

ADSL standard	ITU-T G.992.5, ITU-T G.992.3, ITU-T G.992.1, ANSI T1.413 Issue 2	
G.992.5 (ADSL2+)	Downstream : 24 Mbps	Upstream : 1.3 Mbps
G.992.3 (ADSL2)	Downstream : 12 Mbps	Upstream : 1.3 Mbps
G.DMT	Downstream : 8 Mbps	Upstream : 832 Kbps
AnnexM		

LAN Interface

Standard	IEEE 802.3, IEEE 802.3u
10/100 BaseT	Auto-sense
MDI/MDX support	Yes

WLAN Interface

Standard	IEEE802.11g, backward compatible with 802.11b
Encryption	64, 128-bit Wired Equivalent Privacy (WEP) Data Encryption
Channels	11 Channels (US, Canada)/ 13 Channels (Europe)/ 14 Channels (Japan)
Data Rate	Up to 54Mbps
WPA/WPA2	Yes
IEEE 802.1x	Yes
Afterburner mode (Turbo mode)	Yes (this feature is optional)
WMM	Yes

ATM Attributes

RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Route; RFC 2516 (PPPoE); RFC 1577 (IPoA), Annex M	
Support PVCs	16
AAL type	AAL5
ATM service class	UBR/CBR/VBR
ATM UNI support	UNI3.1/4.0
OAM F4/F5	Yes

Management

SNMP, Telnet, Web-based management, Configuration backup and restoration
Software upgrade via HTTP, TFTP server, or FTP server
Supports TR-069/TR-098/TR-111 for Remote Management

Bridge Functions

Transparent bridging and learning	IEEE 802.1d
VLAN support	Yes
Spanning Tree Algorithm	Yes
IGMP Proxy	Yes

Routing Functions

Static route, RIP, and RIPv2, NAT/PAT, DHCP Server/DHCP Relay/DHCP Client, DNS Proxy, ARP

Security Functions

Authentication protocols PAP, CHAP, TCP/IP/Port filtering rules, Port triggering/Forwarding, Packet and MAC address filtering, Access control, SSH

QoS

L3 policy-based QoS, IP QoS, ToS

Application Passthrough

PPTP, L2TP, IPSec, VoIP, Yahoo messenger, ICQ, RealPlayer, NetMeeting, MSN, X-box, etc

Power Supply

External power adapter	100 - 240 Vac
------------------------	---------------

Environment Condition

Operating temperature	0 ~ 50 degrees Celsius
Relative humidity	5 ~ 95% (non-condensing)

Dimensions

205 mm(W) x 48 mm (H) x 145 mm (D)

Kit Weight (1*CT-5361T, 1*RJ11 cable, 1*RJ45 cable, 1*power adapter, 1*CD-ROM)

1.1 KG

Note: Specifications are subject to change without notice.

Taiwan:
3F-1, No.10, Lane 609, Chung Hsin Road
Section 5, San Chung, Taipei, Taiwan 24159
Tel: 886-2-2999-8261
Fax: 886-2-2999-8497

China:
Room 102, No.8, Lijing Garden, Yushan Town,
Kunshan City, Jiangsu Province, China
Tel: 86-512-57383156, 86-512-57383157,
86-512-57384515
Fax: 86-512-57383155

Spain:
Edif. América II C/Proción, 7 portal 3 bajo H 28023 Madrid,
Spain
Tel: 34-917990403
Fax: 34-913510999

France:
87, Rue du Gouverneur Général Félix Eboué 92130
Issy-les-Moulineaux, France
Tel: 33-1-70715700
Fax: 33-1-70715701

Czech Republic:
TOKOVO, Jankovcova 1518/2, 170 00 Prague 7, Czech Republic
Tel: 420-266-782040
Fax: 420-266-782990

USA:
15375 Barranca Parkway, Suite C-104 Irvine,
CA 92618, USA
Tel: 1-949-7539640
Fax: 1-949-7539020

Canada:
300-1275 West 6th Ave, Vancouver, BC V6H
1A6, Canada
Tel: 1-949-7539640
Fax: 1-949-7539020

Brazil:
Rua Vergueiro, 2087 cj. 101, 04101-000 Sao
Paulo, SP - Brazil
Tel: 55-11-50878831



COMTREND CORPORATION

Global contact: sales@comtrend.com
Website: www.comtrend.com



DS_CT5361T_R1.1_110507